

# Del-Ron®



## Synthetic 5w30 & 0w20 R

The oil: **real synthetic** formulation; **PolyAlphaOlefin (PAO)**.

**Excellent synthetic** lubricating oils, **Excellent Quality !**

**The new technology** additives, **very good performance !**

**Excellent for small diesel engines when 5w30 viscosity is required.**

**Very good soot dissolving property, your engine will stay clean longer and it will maintain it's maximum performance better.**

**For long oil change intervals. The oil will maintain it's superior qualities even when used for a long period. This is extremely important when having long oil change intervals.**

**Manufactured using a high stability viscosity improver. This way the oil has achieved superior qualities; high stability and stability under stress, good endurance against high temperatures and good properties of diminishing the wearing of engine parts.**

**Suitable for catalytic converters(CAT) and particle filters(DPF); low sulphated ash(SAPS) and phosphorous content.**

**So-called LowFriction, ability to lower fuel consumption and reduce wear of engine parts. Do not mix with other oils or additives !**

### Technical information:

|                          |                   |                         |
|--------------------------|-------------------|-------------------------|
| <b>SAE:</b>              | <b>5w30</b>       | <b>0w20</b>             |
| <b>Visc. +40C, cSt</b>   | <b>65</b>         | <b>51</b>               |
| <b>Visc. +100C, cSt</b>  | <b>11,2</b>       | <b>9,28</b>             |
| <b>Visc.index:</b>       | <b>166</b>        | <b>167</b>              |
| <b>Visk.CCS(-30C 5w)</b> | <b>6.050 mPas</b> | <b>6.200 mPas(-35C)</b> |
| <b>Pour Point:</b>       | <b>-42 C</b>      | <b>-48 C</b>            |
| <b>HTHS (+150C)</b>      | <b>3,3 mPas</b>   | <b>2,7 mPas</b>         |
| <b>Sulphate ash:</b>     |                   | <b>0,8 %</b>            |
| <b>Phosphorous:</b>      |                   | <b>0,08 %</b>           |
| <b>TBN</b>               |                   | <b>8,0</b>              |
| <b>Colour:</b>           |                   | <b>Red</b>              |

### 5w30:

**ACEA-16: A5/B5, C2**  
**ACEA-12: A1/B1, A5/B5, C2**  
**ACEA-08: A1/B1, A5/B5, C2/C3**  
**API: (SL) SM / SN / CF**  
**PSA: B71-2290**  
**Renault: RN-0700**  
**VW: 503 / 506**

### 0w20:

**ACEA-16: C5**  
**ACEA-12: A1/B1**  
**ACEA-08: A1/B1**  
**API: SM / SN**  
**Ford: WSS-M2C948-A/B**  
**IISAC-GF6A**  
**VW: 508 / 509**

Values may vary/change, Please note that the properties do not constitute a specification and are not an warranty or guarantee of any properties.

